

Combo Truss Machine Screws

Typically used for Direct Mount



Made from 18-8 passivated stainless steel

| ITEM # | SIZE / MATERIAL |
|------------|-------------------------|
| 25C50MCTS | 1/4-20 X 1/2" 18-8 SS |
| 25C75MCTS | 1/4-20 X 3/4" 18-8 SS |
| 25C100MCTS | 1/4-20 X 1" 18-8 SS |
| 25C125MCTS | 1/4-20 X 1-1/4" 18-8 SS |
| 25C150MCTS | 1/4-20 X 1-1/2" 18-8 SS |
| 25C175MCTS | 1/4-20 X 1-3/4" 18-8 SS |
| 25C200MCTS | 1/4-20 X 2" 18-8 SS |
| 25C250MCTS | 1/4-20 X 2-1/2" 18-8 SS |
| 25C300MCTS | 1/4-20 X 3" 18-8 SS |
| 25C350MCTS | 1/4-20 X 3-1/2" 18-8 SS |
| 25C400MCTS | 1/4-20 X 4" 18-8 SS |
| 25C500MCTS | 1/4-20 X 5" 18-8 SS |
| 25C600MCTS | 1/4-20 X 6" 18-8 SS |

Applications: Install into a 1/4-20 anchor wood bushing or other insert with a #3 Phillips bit.

Key-Hole Washers



| ITEM # | SIZE / DESCRIPTION |
|--------|--|
| /KEY | ALUMINUM WASHER FOR USE WITH A 1/4-20 BOLT |

Commonly used with Combo Truss Machine Screws.